



NATURA LUXURY VINYL FLOORING
TECHNICAL SPECIFICATIONS

	Metric	Imperial
Gauge	3.00 mm	0.118"
Sizes		
▪ Tiles	457 mm x 457 mm	18" x 18"
▪ Planks	101 mm x 915 mm	4" x 36"
Wear Layer Thickness	0.2mm (0.008")	
ASTM D 3389 – Abrasion Resistance (H-22/ 500 g @ 1,000 cycles)	Pass	
ASTM E 648 – Critical Radiant Flux CRF (W/cm ²)	> 0.45	
ASTM E 662 – Smoke Density	≤ 450	
ASTM F 925 – Chemical Resistance	Meets requirements – (details upon request)	
ASTM F 970 – Static Load (modified @ 2,500 psi)	≤ 0.005"	
ASTM F 1700 – Solid Vinyl Floor Tile	Class III, Type A or B	
ASTM F 1914 – Residual Indentation	≤ 8%	
ASTM F 2055 – Squareness	0.010" maximum	
Indoor Air Quality (IAQ): Volatile Organic Compounds (VOC's)	FloorScore Certified by SCS Certification Registration Number SCS-FS-03325	
Maintenance	Very low	
PU (Polyurethane) surface treatment	Facilitates maintenance	
Adhesives: PS-30 AD-535	Regular traffic Heavy traffic/rolling loads	
Limited Wear Warranty	5 years for light commercial installations 10 years for residential installations	

Please note that technical web site documents prevail.

