

MARATHON® OASIS®
SHEET RUBBER
TECHNICAL SPECIFICATIONS

	Metric	Imperial
Gauge	2 mm 3 mm	0.080" 0.118"
Size	1.5 m x 15.2 m	60" nominal x 50'
Product Classification: Rubber Sheet Floor	ASTM F 1859, Type I (Homogeneous)	
ASTM D 2047 – Static Coefficient of Friction (leather)	≥ 0.5	
ASTM E 492 / E 989 – Impact Insulation Class (IIC)	60 (3 mm) (with suspended ceilings)	
ASTM E 648 – Critical Radiant Flux CRF (W/cm ²)	≥ 0.45	
ASTM E 662 – Smoke Density	≤ 450	
ASTM F 925 – Chemical Resistance	Meets requirements (details upon request)	
ASTM F 970 – Static Load (modified at 2000 psi)	≤ 0.005"	
ASTM F 1514 – Heat Stability (ΔE ≤ 8.0)	Pass	
ASTM F 1515 – Light Stability (ΔE ≤ 8.0)	Pass	
ASTM G 21 – Antimicrobial Resistance Test	Pass (28 days)	
Indoor Air Quality (IAQ): Volatile Organic Compounds (VOC's)	FloorScore Certified by SCS Certification Registration Number SCS-FS-01492	
New York City Fire Prevention Code	Accepted under section 27-348	
New York State Fire Prevention Code	Complies with Article 15, Part 1120	
Adhesives: AD-777 AD-535	Regular traffic Heavy rolling loads & under patients' beds	
Limited Wear Warranty	10 years	
Resistance to oils and greases		
Marathon® Oasis® is not recommended for environments where it could be exposed to oils and greases, whether mineral, animal or vegetable.		
Antimicrobial		
IMPORTANT: All our Oasis Rubber Flooring, through its composition and without the use of antimicrobial chemicals, does not promote microbial growth.		

Please note that technical web site documents prevail.

