



AmericanBiltrite
Flooring

ABPURE® STAIR TREADS – RUBBER FLOORING

TECHNICAL SPECIFICATIONS

	Metric		Imperial	
TREADS: Regular Round/Hammered & Regular Round/Hammered with Visually Impaired Safety Strip				
Profiles	Round	Hammered	Round	Hammered
Gauge	3.17 mm	3.5mm	1/8"	0.140"
Sizes	0.914 m		36"	
	1.219 m		48"	
	1.828 m		72"	
Depth	314 mm		12-3/8"	
Nosing Depth	47 mm ADA compliant		1-7/8" ADA compliant	
Nosing Radius	6 mm ADA compliant		1/4" ADA compliant	
TREADS & RISERS: One-Piece Round/Hammered & One-Piece Round/Hammered with Visually Impaired Safety Strip				
Gauge	3.17 mm	3.5mm	1/8"	0.140"
Sizes	0.914 m		36"	
	1.219 m		48"	
	1.828 m		72"	
Depth	482 mm		19"	
Nosing Depth	47 mm ADA compliant		1-7/8" ADA compliant	
Nosing Radius	6 mm ADA compliant		1/4" ADA compliant	
ASTM E 648 – Critical Radiant Flux CRF (W/cm ²)	> 0.45			
ASTM E 662 – Smoke Density	≤ 450			
ASTM F 925 – Chemical Resistance	Meets requirements (details upon request)			
ASTM F 1514 – Heat Stability	≤ 8			
ASTM F 1515 – Light Stability	≤ 8			
ASTM F 2169 – Resilient Stair Treads	Type TS Rubber Vulcanized Thermoset – Class 2 Group 1 & 2 (Visually Impaired Safety Strip)			
Indoor Air Quality (IAQ) Volatile Organic Compounds (VOC's)	FloorScore® Certified by SCS Certification Registration Number SCS-FS-01492a			
Adhesives: AD-777, AD-535 & Zip-Step	Regular traffic			
Nosing compound: NC-888	Regular traffic			
Limited Wear Warranty	10 years			
Resistance to oils and greases ABPURE® is not recommended for environments where it could be exposed to oils and greases, whether mineral, animal or vegetable.				
Antimicrobial/Antifungal IMPORTANT: All ABPURE® rubber flooring contains inhibitors that gives this flooring antimicrobial and antifungal properties.				

Please note that technical web site documents prevail.

