



**American Biltrite**  
Flooring

## MARATHON PLUS RUBBER FLOORING

### TECHNICAL SPECIFICATIONS

	Metric	Imperial
Gauge	3.17 mm	1/8"
Sizes	910 mm x 910 mm 454 mm x 454 mm Micro Ground™	35-13/16" x 35-13/16" 17-7/8" x 17-7/8" Micro Ground™
ASTM D 471 – Oil & Grease Resistance	Oil #1 – Excellent Oil #3 – Excellent	
ASTM F 1344 – Rubber Floor Tile	Class I, A	
ASTM D 2240 – Hardness (Shore A)	≥ 85	
ASTM D 3389 – Abrasion Resistance (H-18 500 g @ 1,000 cycles)	Pass	
ASTM E 648 – Critical Radiant Flux CRF (W/cm <sup>2</sup> )	> 0.45	
ASTM E 662 – Smoke Density	≤ 450	
ASTM F 925 – Chemical Resistance	Excellent	
Cigarette Burn & Solder Resistance	Excellent	
Indoor Air Quality (IAQ) Volatile Organic Compounds (VOC's)	FloorScore Certified by SCS Certification Registration Number SCS-FS-01492	
Adhesive: AD-535	All installations	
Limited Wear Warranty	10 years	

Please note that technical web site documents prevail.

