

## MARATHON® RUBBER STAIR TREADS TECHNICAL SPECIFICATIONS

	Metric		Imperial	
<b>TREADS: Regular Round/Hammered &amp; Regular Round/Hammered with Visually Impaired Safety Strip</b>				
Profiles	<b>Round</b>	<b>Hammered</b>	<b>Round</b>	<b>Hammered</b>
Gauge	3.17 mm	3.5mm	1/8"	0.140"
Sizes	0.914 m 1.219 m 1.828 m		36" 48" 72"	
Depth	314 mm		12-3/8"	
Nosing Depth	47 mm ADA compliant		1-7/8" ADA compliant	
Nosing Radius	6 mm ADA compliant		1/4" ADA compliant	
<b>TREADS &amp; RISERS: One-Piece Round/Hammered &amp; One-Piece Round/Hammered with Visually Impaired Safety Strip</b>				
Gauge	3.17 mm	3.5mm	1/8"	0.140"
Sizes	0.914 m 1.219 m 1.828 m		36" 48" 72"	
Depth	482 mm		19"	
Nosing Depth	47 mm ADA compliant		1-7/8" ADA compliant	
Nosing Radius	6 mm ADA compliant		1/4" ADA compliant	
Product Classification:	Type TS Rubber Vulcanized Thermoset – Class 2, Group 1 & 2 (Visually Impaired Safety Strip)			
ASTM F 2169 - Standard Specification for Resilient Stair Treads	≥ 0.45			
ASTM E 648 – Critical Radiant Flux CRF (W/cm <sup>2</sup> )	≤ 450			
ASTM E 662 – Smoke Density	Meets requirements (details upon request)			
ASTM F 925 – Chemical Resistance	ΔE ≤ 8.0			
ASTM F 1514 – Heat Stability	FloorScore® Certified by SCS Certification Registration Number SCS-FS-01492			
Indoor Air Quality (IAQ) Volatile Organic Compounds (VOC's)	Regular traffic			
Adhesives: AD-777, AD-535 & Zip-Step	Regular traffic			
Nosing compound: NC-888	10 years			
Limited Wear Warranty	Resistance to oils and greases			
MARATHON® is not recommended for environments where it could be exposed to oils and greases, whether mineral, animal or vegetable.				
Antimicrobial				
<b>IMPORTANT:</b> All MARATHON® rubber flooring, through its composition and without the use of antimicrobial chemicals, does not promote microbial growth.				

Please note that technical web site documents prevail.

