



# Oasis

## SPECIFICATIONS

Roll Size	1.5 m X 15.2 m (60" nominal x 50')
Gauge	2mm
Colors	32
Surface Profile	Paper textured look
ASTM F-1859	Complies Type 1
ASTM E-648/NFPA 253 – Fire Resistance	Class 1
Critical Radiant Flux CRF	>1.10
ASTM E-662 – Smoke Density	Class 1 $\leq$ 450
New York State Fire Prevention Code	Complies with Article 15, Part 1120
New York City Fire Prevention Code	Accepted under section 27-348
ASTM D-3389 Abrasion Resistance (H-18 500 gr @ 1,000 cycles)	0.5g
ASTM D-2047 - Static Coefficient of Friction	0.75
ASTM E-2179 - Impact Sound Transmission	16 dB
ASTM E-492 - Airborne Sound	16 dB
ASTM D-2240 - Hardness	$\geq$ 85 Shore A
ASTM F-970 - Static Load (modified)	1,100 PSI
ASTM D-297 - Density	1.72g
ASTM D-412 - Tensile	1,000 PSI
ASTM D-412 - Elongation	170%
ASTM D-624 - Tear Die	190 lb/in
ASTM F-925 - Chemical Resistance	Complies (Available on request)
VOCs (Volatile Organic Compounds)	Very Low





# Oasis

## SPECIFICATIONS

ASTM F-1515 - Light Stability	Complies
ASTM F-1514 - Heat Stability	Complies
ESD S. 7. 1 - Electrical Resistance	$\geq 10^{10}$ ohms
Indoor Air Quality	FloorScore Certified by SCS, Certification No. SCS-FS-01492
Limited Wear Warranty	10 years
<b>ANTIBACTERIAL</b>	
<b>IMPORTANT:</b> All Oasis rubber flooring contains <b>naturally</b> occurring inhibitors that resist the growth of bacteria, fungus and mould.	

