



MIRRA Luxury Vinyl Flooring SPECIFICATIONS

	Metric	Imperial
Gauge	3.0 mm	0.1181"
Size	Tiles 305 x 610 mm 457 x 457 mm 457 x 915 mm	12" x 24" 18" x 18" 18" x 36"
<ul style="list-style-type: none"> ▪ Travertine ▪ Slate, Marble, Granite, Concrete, Terrazzo, Cork ▪ Metallic 	Planks 101 x 915 mm 152 x 915 mm	4" x 36" 6" x 36"
<ul style="list-style-type: none"> ▪ Exotic, Wood Plank (WP000) & Bamboo Series ▪ Rustic WP600 Series (Premium) 		
Borders	101 x 915 mm	4" x 36"
Inserts /Keys	101 x 101 mm	4" x 4"
Strip-C, Strip-G, Strip-M, Strip-S	5 x 915 mm	13/64" x 36"
Colors	Slate 8 Marble 2 Granite 6 Concrete 1 Travertine 1 Terrazzo 1 Metallic 3	Exotic 11 Wood Plank 7 Rustic 5 Bamboo 5 Cork 1 Borders 5 Inserts/Keys 5 Grout Strips 4
ASTM F 1303 – Type I Grade 1 Wear Layer	0.7 mm	
ASTM F 1700 – Composition	Class III, Type A or B	
ASTM F 540 – Squareness	0.006	
ASTM D 2240 – Hardness, Shore D	59	
ASTM E 662 – Smoke Density	Class 1 <450	
ASTM E 648 / NFPA 253 – Fire Resistance	Class 1	
ASTM D 3389 – Abrasion Resistance	0.122gm loss	
ASTM D 1894 / ASTM D 2047 - Static Coefficient of Friction	0.75	
ASTM F 1700 / F 1914 test method – Indentation	Initial 21% Residual 4.8%	
ASTM F 970 – Static Load	2,500 PSI	
ASTM F 925 – Chemical Resistance	Exceeds – List available on request	
Indoor Air Quality (VOC's)	Very Low	
Maintenance	Very Low	
PU (Polyurethane) surface treatment	Assists in making maintenance easier	
Limited Wear Warranty	20 years warranty for Commercial installations Lifetime warranty for Residential installations	

