



AB-362

| | |
|---------|------------|
| GRADE | Commercial |
| FINISH | Smooth |
| POWDER | Yes |
| TRIMMED | Yes |
| COLOR | Black |

TECHNICAL SPECIFICATIONS

**SPECIFICATION ASTM D2240 | Z1= HARDNESS 60 +/- 5 SHORE A
POLYMER: NITRILE (NBR) BLEND**

| ASTM | DESCRIPTION | VALUE |
|---------------------------------------|--|---------------------------------|
| D2240 | HARDNESS (shore A) | 60 +/- 5 |
| D412 | TENSILE (psi) | 800 min. |
| | ULTIMATE ELONGATION (%) | 350 min. |
| D395 (Method B) | COMPRESSION SET 22 hrs @ 100°C (212°F) | 60% max. |
| D471 | OIL RESISTANCE Oil #3, 70 hrs @ 100°C (212°F) | Volume (%): 120 max. |
| TEMPERATURE RANGE (general guideline) | | -30° to 190°F (-34° to 88°C) |

Maximum pieces per roll: 2

Minimum piece length: 10'

Width tolerance: -0 / +1"

Material is within commercial sheet rubber gauge tolerances.

The documentation for sheet rubber gauge tolerances is published on our website. Please ensure the product meets your application specification prior to order placement. Specifications are subject to change without notice. The website version prevails.

| | GAUGE IN (MM) | WIDTH IN (MM) | SURFACE/ROLL SFT (M ²) | LENGTH/ROLL LFT (M) | WEIGHT/ROLL LBS (KG) |
|-------------------------|------------------|------------------|---------------------------------------|------------------------|-------------------------|
| 362-04-362 | 1/16 (1.60) | 36 (914.4) | 300 (27.87) | 100 (30.48) | 132 (59.9) |
| 362-04-482 | 1/16 (1.60) | 48 (1219.2) | 400 (37.16) | 100 (30.48) | 196 (88.9) |
| 362-08-362 | 1/8 (3.20) | 36 (914.4) | 150 (13.93) | 50 (15.24) | 147 (66.7) |
| 362-08-482 | 1/8 (3.20) | 48 (1219.2) | 200 (18.58) | 50 (15.24) | 196 (88.9) |
| 362-12-482 | 3/16 (4.80) | 48 (1219.2) | 160 (14.86) | 40 (12.19) | 235 (106.6) |
| 362-16-362 | 1/4 (6.35) | 36 (914.4) | 120 (11.15) | 40 (12.19) | 224 (101.6) |
| 362-16-482 | 1/4 (6.35) | 48 (1219.2) | 160 (14.86) | 40 (12.19) | 298 (133.2) |
| 362-24-482 ¹ | 3/8 (9.50) | 48 (1219.2) | 120 (11.15) | 30 (9.14) | 353 (160.1) |
| 362-32-482 ¹ | 1/2 (12.70) | 48 (1219.2) | 120 (11.15) | 30 (9.14) | 470 (213.2) |

¹ Made to order.

