



**U.S. MILITARY
SPECIFICATION GRADE
MIL-6855 CLASS 2, GRADE 60**

GRADE	Military
FINISH	Smooth
POWDER	Yes
TRIMMED	Yes
COLOR	Black

TECHNICAL SPECIFICATIONS

POLYMER: NEOPRENE(CR)

ASTM	DESCRIPTION	VALUE
	SPECIFIC GRAVITY (gr/cc)	1.31
D2240	HARDNESS (shore A)	60
D412	TENSILE (psi)	1500 min.
	ULTIMATE ELONGATION (%)	300 min.
TEMPERATURE RANGE (general guideline)		-22° to 212°F (-30° to 100°C)

Material is within commercial sheet rubber gauge tolerances.

The documentation for sheet rubber gauge tolerances is published on our website. Please ensure the product meets your application specification prior to order placement. Specifications are subject to change without notice. The website version prevails.

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M ²)	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
20M-08-362 ¹	1/8 (3.20)	36 (914.4)	117 (10.87)	39 (11.88)	101 (45.8)

¹ Made to order.

