

**AB-141 BLAST®**

GRADE	Industrial
FINISH	Paper (matte one side)
POWDER	No
TRIMMED	Yes
COLOR	White

TECHNICAL SPECIFICATIONS

SPECIFICATION ASTM D2000: 2AA425A13F17
POLYMER: NATURAL RUBBER (NR)

ASTM	DESCRIPTION	VALUE
	SPECIFIC GRAVITY (gr/cc)	1.11
D2240	HARDNESS (shore A)	40
D412	TENSILE (psi)	2500 min.
	ULTIMATE ELONGATION (%)	400 min.
D2137	COLD TEMPERATURE	-40°C/°F min.
D395 (Method B)	COMPRESSION SET 22 hrs @ 70°C (158°F)	50% max.
D573	HEAT AGING 70 hrs @ 70°C (158°F)	Hardness: +/-15 Tensile (%): +/-30 max. Elongation (%): -50 max.
TEMPERATURE RANGE (general guideline)		-20° to 180°F (-29° to 82°C)

Maximum pieces per roll: 1

Minimum piece length: 7'

Width tolerance: -0.5 / +1"

Material is within commercial sheet rubber gauge tolerances.

The documentation for sheet rubber gauge tolerances is published on our website.

Typical values do not constitute a specification.

Please ensure the product meets your application specification prior to order placement.

Specifications are subject to change without notice. The website version prevails.

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M ²)	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
47P-16-482 ¹	1/4 (6.35)	48 (1219.2)	200 (18.58)	50 (15.24)	288 (130.6)

¹ Made to order.

