

**ULTRACERAMIC®/™ CONTRACT**  
**ENGINEERED STONE**  
TECHNICAL SPECIFICATIONS

	Metric	Imperial
Gauge	4.00 mm	0.157"
Sizes	303.6 mm x 608 mm 456 mm x 456 mm	Nominal 12" x 24" (11.953" x 23.937") Nominal 18" x 18" (17.953" x 17.953")
Product Classification: ASTM F3261 – Resilient Flooring in Modular Format with Rigid Polymeric Core	Class I, Type B, Grade I with Backing Class A	
Wear Layer Thickness	0.5 mm (0.020")	
Edge Profile	Superior Rounded Edge	
ASTM D2047 – Static Coefficient of Friction (leather)	≥ 0.5	
ASTM E648 – Critical Radiant Flux CRF (W/cm <sup>2</sup> )	≥ 0.45	
ASTM E662 – Smoke Density	≤ 450	
ASTM F925 – Chemical Resistance	Exceeds	
ASTM F970 – Static Load (modified at 1,500 psi)	≤ 0.005"	
ASTM F1514 – Resistance to Heat	ΔE ≤ 8	
ASTM F1515 – Resistance to Light	ΔE ≤ 8	
ASTM F1914 - Indentation	Residual < 8%	
Adhesives: PS-30 AD-590	Regular traffic Heavy Traffic / Heavy Rolling Loads	
Grout	UltraCeramic Premixed Grout (INSTALL GROUTED ONLY)	
Indoor Air Quality (IAQ): Volatile Organic Compounds (VOC's)	FloorScore Certified by SCS Certification Registration Number SCS-FS-03325	
Limited Wear Warranty	10 years for commercial installations	

Please note that technical web site documents prevail.

