



AB-951 NEOPRENE CLOTH INSERTED PACKING

GRADE	Industrial
FINISH	Smooth
POWDER	Yes
TRIMMED	Yes
COLOR	Black
FABRIC	Polyester

TECHNICAL SPECIFICATIONS

**SPECIFICATION ASTM D2000: 1BC706Z1 | Z1= HARDNESS 65 +/- 5 SHORE A
POLYMER: NITRILE, STYRENE-BUTADIENE, NEOPRENE (NBR/SBR/CR)**

ASTM	DESCRIPTION	VALUE
	SPECIFIC GRAVITY (gr/cc)	1.45
D2240	HARDNESS (shore A)	65 +/-5
D412	TENSILE (psi)	600 min.
	ULTIMATE ELONGATION (%)	300 min.
D395B	COMPRESSION SET	22 hrs @ 100°C (212°F) 80% max.
D573	HEAT AGING	70 hrs @ 100°C (212°F) Changed Hardness: +/-15 points max. Tensile: +/-30% max. Elongation: -50% max.
D471	OIL AGING #3	70 hrs @ 100°C Volume changed: 120% max.
TEMPERATURE RANGE (general guideline)		-20° to 190°F (-29° to 88°C)

Mullen Burst 1 Ply: 300 psi typical

Maximum pieces per roll: 2 (exception 1/32" & 1/8" x 72 = 3 pieces)

Minimum piece length: 5'

Width tolerance: -0 / +1"

Fabric 2 oz. polyester

Material is within commercial sheet rubber gauge tolerances.

Typical values do not constitute a specification.

Please ensure the product meets your application specification prior to order placement.

Specifications are subject to change without notice. The website version prevails.

AB-951 NEOPRENE CLOTH INSERTED PACKING

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M ²)	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
121-08-362	1/8 (3.20) 1 PLY	36 (914.4)	150 (13.93)	50 (15.24)	139 (63.1)
121-08-482	1/8 (3.20) 1 PLY	48 (1219.2)	200 (18.58)	50 (15.24)	185 (83.9)
121-08-722	1/8 (3.20) 1 PLY	72 (1828.8)	300 (27.87)	50 (15.24)	277 (125.6)
121-12-362 ¹	3/16 (4.80) 2 PLY	36 (914.4)	120 (11.15)	40 (12.19)	165 (74.8)
121-16-482 ¹	1/4 (6.35) 2 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	299 (135.6)
123-02-482	1/32 (0.80) 1 PLY	48 (1219.2)	800 (74.32)	200 (60.96)	151 (68.5)
123-04-362 ¹	1/16 (1.60) 1 PLY	36 (914.4)	300 (27.87)	100 (30.48)	142 (64.4)
123-04-482	1/16 (1.60) 1 PLY	48 (1219.2)	400 (37.16)	100 (30.48)	190 (86.2)
123-08-362 ¹	1/8 (3.20) 2 PLY	36 (914.4)	150 (13.93)	50 (15.24)	136 (61.7)
123-08-482	1/8 (3.20) 2 PLY	48 (1219.2)	200 (18.58)	50 (15.24)	181 (82.1)
123-12-362 ¹	3/16 (4.80) 3 PLY	36 (914.4)	120 (11.15)	40 (12.19)	164 (74.4)
123-12-482	3/16 (4.80) 3 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	218 (98.9)
123-16-482	1/4 (6.35) 4 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	274 (124.3)

¹ Made to order.