



ABPURE®
RUBBER STAIR TREADS
TECHNICAL SPECIFICATIONS

	Metric		Imperial	
TREADS: Regular Round/Hammered & Regular Round/Hammered with Visually Impaired Safety Strip				
Profiles	Round	Hammered	Round	Hammered
Gauge	3.17 mm	3.5 mm	1/8"	0.140"
Sizes	0.914 m		36"	
	1.219 m		48"	
	1.828 m		72"	
Depth	314 mm		12-3/8"	
Nosing Depth	47 mm ADA compliant		1-7/8" ADA compliant	
Nosing Radius	6 mm ADA compliant		1/4" ADA compliant	
TREADS & RISERS: One-Piece Round/Hammered & One-Piece Round/Hammered with Visually Impaired Safety Strip				
Gauge	3.17 mm	3.5 mm	1/8"	0.140"
Sizes	0.914 m		36"	
	1.219 m		48"	
	1.828 m		72"	
Depth	482 mm		19"	
Nosing Depth	47 mm ADA compliant		1-7/8" ADA compliant	
Nosing Radius	6 mm ADA compliant		1/4" ADA compliant	
Product Classification: ASTM F2169 - Standard Specification for Resilient Stair Treads	Type TS Rubber Vulcanized Thermoset – Class 2, Group 1 & 2 (Visually Impaired Safety Strip)			
ASTM E648 – Critical Radiant Flux CRF (W/cm ²)	≥ 0.45			
ASTM E662 – Smoke Density	≤ 450			
ASTM F925 – Chemical Resistance	Meets requirements (details upon request)			
ASTM F1514 – Heat Stability	ΔE ≤ 8.0			
ASTM F1515 – Light Stability	ΔE ≤ 8.0			
Indoor Air Quality (IAQ) Volatile Organic Compounds (VOC's)	FloorScore® Certified by SCS Certification Registration Number SCS-FS-01492			
Adhesives: AD-777, AD-590 & Zip Step	Regular traffic			
Nosing compound: NC 888	Regular traffic			
Limited Wear Warranty	10 years			
Resistance to oils and greases ABPURE® is not recommended for environments where it could be exposed to oils and greases, whether mineral, animal or vegetable.				
Antimicrobial IMPORTANT: All ABPURE® Rubber flooring, through its composition and without the use of antimicrobial chemicals, does not promote microbial growth.				

Please note that technical web site documents prevail.

