



# IM-950 NEOPRENE CLOTH INSERTED PACKING

GRADE	Commercial
FINISH	Smooth
POWDER	No
TRIMMED	Yes
COLOR	Black
FABRIC	Nylon

## TECHNICAL SPECIFICATIONS

SPECIFICATION ASTM D2240 | Z1= HARDNESS 65 +/-7 SHORE A  
POLYMER: NEOPRENE BLEND

ASTM	DESCRIPTION	VALUE
D2240	HARDNESS (shore A)	65 +/- 7
D412	TENSILE (psi)	600 typical
TEMPERATURE RANGE (general guideline)		-20° to 190°F (-29° to 88°C)

**Mullen Burst 1 Ply: 300 psi typical**

**Maximum pieces per roll: 1**

**Width tolerance: +/-1"**

**Durometer Tolerance: +/-7 points**

**Fabric: Nylon**

**Material is within commercial sheet rubber gauge tolerances.**

Typical values do not constitute a specification.

Please ensure the product meets your application specification prior to order placement.

Specifications are subject to change without notice. The website version prevails.

Physical properties based on rubber only.

# IM-950 NEOPRENE CLOTH INSERTED PACKING

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M <sup>2</sup> )	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
103-04-362 <sup>1</sup>	1/16 (1.60) 1 PLY	36 (914.4)	300 (27.87)	100 (30.48)	136 (61.7)
103-04-482	1/16 (1.60) 1 PLY	48 (1219.2)	400 (37.16)	100 (30.48)	190 (86.3)
103-08-362 <sup>1</sup>	1/8 (3.20) 2 PLY	36 (914.4)	150 (13.93)	50 (15.24)	136 (61.7)
103-08-482	1/8 (3.20) 2 PLY	48 (1219.2)	200 (18.58)	50 (15.24)	190 (86.3)
103-12-362	3/16 (4.80) 3 PLY	36 (914.4)	120 (11.15)	40 (12.19)	164 (74.4)
103-12-482 <sup>1</sup>	3/16 (4.80) 3 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	218 (98.9)
103-16-362 <sup>1</sup>	1/4 (6.35) 4 PLY	36 (914.4)	120 (11.15)	40 (12.19)	218 (98.9)
103-16-482 <sup>1</sup>	1/4 (6.35) 4 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	291 (132.0)
104-08-362	1/8 (3.20) 1 PLY	36 (914.4)	150 (13.93)	50 (15.24)	143 (64.7)
104-08-482	1/8 (3.20) 1 PLY	48 (1219.2)	200 (18.58)	50 (15.24)	190 (86.3)
104-12-362 <sup>1</sup>	3/16 (4.80) 2 PLY	36 (914.4)	120 (11.15)	40 (12.19)	164 (74.4)
104-12-482	3/16 (4.80) 2 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	228 (103.4)
104-16-362 <sup>1</sup>	1/4 (6.35) 3 PLY	36 (914.4)	120 (11.15)	40 (12.19)	218 (98.9)
104-16-482	1/4 (6.35) 3 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	304 (137.9)

<sup>1</sup> Made to order.