



# IM-166 SKIRTBOARD

## TECHNICAL SPECIFICATIONS

SPECIFICATION ASTM D2240 | Z1= HARDNESS 60 +/-7 SHORE A  
POLYMER: STYRENE-BUTADIENE (SBR)

GRADE	Commercial
FINISH	Smooth
POWDER	No
TRIMMED	Yes
COLOR	Black

ASTM	DESCRIPTION	VALUE
D2240	HARDNESS (shore A)	60 +/- 7
D412	TENSILE (psi)	500 typical
	ULTIMATE ELONGATION (%)	300 typical
TEMPERATURE RANGE (general guideline)		-20° to 180°F (-29° to 82°C)

**Maximum pieces per roll: 1**

**Width tolerance: +/-0.177"**

**Durometer tolerance: +/-7 points**

**Material is within commercial sheet rubber gauge tolerances.**

The documentation for sheet rubber gauge tolerances is published on our website. Typical values do not constitute a specification. Please ensure the product meets your application specification prior to order placement. Specifications are subject to change without notice. The website version prevails.

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M <sup>2</sup> )	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
166-04-484	1/16 (1.60)	48 (1219.2)	---	50 (15.24)	90 (40.8)
166-08-364 <sup>1</sup>	1/8 (3.20)	36 (914.4)	---	50 (15.24)	134 (60.8)
166-08-484	1/8 (3.20)	48 (1219.2)	---	50 (15.24)	178 (80.7)
166-08-724 <sup>1</sup>	1/8 (3.20)	72 (1828.8)	---	50 (15.24)	188 (85.3)
166-16-034 <sup>1</sup>	1/4 (6.35)	3 (76.2)	---	50 (15.24)	22 (9.9)
166-16-044	1/4 (6.35)	4 (101.6)	---	50 (15.24)	30 (13.6)
166-16-064	1/4 (6.35)	6 (152.4)	---	50 (15.24)	44 (20.1)
166-16-084	1/4 (6.35)	8 (203.2)	---	50 (15.24)	59 (26.8)
166-16-104 <sup>1</sup>	1/4 (6.35)	10 (254.0)	---	50 (15.24)	74 (33.6)
166-16-124	1/4 (6.35)	12 (304.8)	---	50 (15.24)	88 (39.9)
166-16-484	1/4 (6.35)	48 (1219.2)	---	50 (15.24)	354 (160.6)
166-24-034 <sup>1</sup>	3/8 (9.50)	3 (76.2)	---	50 (15.24)	33 (14.9)
166-24-044	3/8 (9.50)	4 (101.6)	---	50 (15.24)	44 (19.9)
166-24-054 <sup>1</sup>	3/8 (9.50)	5 (127.0)	---	50 (15.24)	55 (24.9)
166-24-064	3/8 (9.50)	6 (152.4)	---	50 (15.24)	66 (29.9)
166-24-084	3/8 (9.50)	8 (203.2)	---	50 (15.24)	88 (39.9)
166-24-104 <sup>1</sup>	3/8 (9.50)	10 (254.0)	---	50 (15.24)	110 (49.9)
166-24-124	3/8 (9.50)	12 (304.8)	---	50 (15.24)	132 (59.9)
166-24-484	3/8 (9.50)	48 (1219.2)	---	50 (15.24)	528 (239.5)
166-32-034 <sup>1</sup>	1/2 (12.70)	3 (76.2)	---	50 (15.24)	44 (19.9)
166-32-044	1/2 (12.70)	4 (101.6)	---	50 (15.24)	58 (26.3)
166-32-054	1/2 (12.70)	5 (127.0)	---	50 (15.24)	73 (33.1)

<sup>1</sup> Made to order.

# IM-166 SKIRTBOARD

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M <sup>2</sup> )	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
166-32-064	1/2 (12.70)	6 (152.4)	---	50 (15.24)	88 (39.9)
166-32-084	1/2 (12.70)	8 (203.2)	---	50 (15.24)	117 (53.1)
166-32-104	1/2 (12.70)	10 (254.0)	---	50 (15.24)	146 (66.2)
166-32-124	1/2 (12.70)	12 (304.8)	---	50 (15.24)	175 (79.4)
166-32-484	1/2 (12.70)	48 (1219.2)	---	50 (15.24)	702 (318.4)
166-48-034 <sup>1</sup>	3/4 (19.00)	3 (76.2)	---	50 (15.24)	66 (29.8)
166-48-044 <sup>1</sup>	3/4 (19.00)	4 (101.6)	---	50 (15.24)	88 (39.9)
166-48-064	3/4 (19.00)	6 (152.4)	---	50 (15.24)	132 (59.9)
166-48-084	3/4 (19.00)	8 (203.2)	---	50 (15.24)	176 (79.8)
166-48-104 <sup>1</sup>	3/4 (19.00)	10 (254.0)	---	50 (15.24)	219 (99.3)
166-48-124	3/4 (19.00)	12 (304.8)	---	50 (15.24)	263 (119.3)
166-48-484	3/4 (19.00)	48 (1219.2)	---	50 (15.24)	1054 (478.1)
166-64-034	1 (25.40)	3 (76.2)	---	50 (15.24)	88 (39.9)
166-64-044 <sup>1</sup>	1 (25.40)	4 (101.6)	---	50 (15.24)	117 (53.1)
166-64-064	1 (25.40)	6 (152.4)	---	50 (15.24)	175 (79.4)
166-64-084	1 (25.40)	8 (203.2)	---	50 (15.24)	234 (106.1)
166-64-104	1 (25.40)	10 (254.0)	---	50 (15.24)	292 (132.5)
166-64-124	1 (25.40)	12 (304.8)	---	50 (15.24)	351 (159.2)
166-64-484	1 (25.40)	48 (1219.2)	---	50 (15.24)	1404 (636.9)
166-65-104 <sup>1</sup>	1 1/4 (31.75)	10 (254.0)	---	50 (15.24)	355 (161.0)
166-66-034 <sup>1</sup>	1 1/2 (38.10)	3 (76.2)	---	50 (15.24)	131 (59.4)
166-66-044 <sup>1</sup>	1 1/2 (38.10)	4 (101.6)	---	50 (15.24)	175 (79.4)
166-66-064 <sup>1</sup>	1 1/2 (38.10)	6 (152.4)	---	50 (15.24)	263 (119.3)
166-66-084	1 1/2 (38.10)	8 (203.2)	---	50 (15.24)	351 (159.2)
166-66-104	1 1/2 (38.10)	10 (254.0)	---	50 (15.24)	439 (199.1)
166-66-124	1 1/2 (38.10)	12 (304.8)	---	50 (15.24)	527 (239.0)
166-66-484 <sup>1</sup>	1 1/2 (38.10)	48 (1219.2)	---	50 (15.24)	2341 (1061.1)
166-68-484 <sup>1</sup>	2 (50.80)	48 (1219.2)	---	50 (15.24)	2803 (1271.4)

<sup>1</sup> Made to order.