



IM-618

GRADE	Industrial
FINISH	Smooth
POWDER	No
TRIMMED	Yes
COLOR	Red

TECHNICAL SPECIFICATIONS

SPECIFICATION ASTM D2240 | Z1= HARDNESS 75 +/-7 SHORE A
POLYMER: STYRENE-BUTADIENE (SBR)

ASTM	DESCRIPTION	VALUE
D2240	HARDNESS (shore A)	75 +/- 7
D412	TENSILE (psi)	400 typical
	ULTIMATE ELONGATION (%)	220 typical
TEMPERATURE RANGE (general guideline)		-20° to 180°F (-29° to 82°C)

Maximum pieces per roll: 1

Width tolerance: -0 / +1"

Durometer tolerance: +/-7 points

Material is within commercial sheet rubber gauge tolerances.

Typical values do not constitute a specification.

Please ensure the product meets your application specification prior to order placement.

Specifications are subject to change without notice. The website version prevails.

IM-618

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M ²)	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
110-04-368	1/16 (1.60)	36 (914.4)	210 (19.51)	70 (21.33)	119 (53.9)
110-04-488	1/16 (1.60)	48 (1219.2)	200 (18.58)	50 (15.24)	113 (51.3)
110-04-728 ¹	1/16 (1.60)	72 (1828.8)	420 (39.02)	70 (21.33)	234 (106.1)
110-06-368 ¹	3/32 (2.38)	36 (914.4)	165 (15.33)	55 (16.76)	140 (63.5)
110-06-488 ¹	3/32 (2.38)	48 (1219.2)	160 (14.86)	40 (12.19)	136 (61.7)
110-06-728	3/32 (2.38)	72 (1828.8)	330 (30.66)	55 (16.76)	280 (127.0)
110-08-368	1/8 (3.20)	36 (914.4)	105 (9.75)	35 (10.66)	119 (54.0)
110-08-488	1/8 (3.20)	48 (1219.2)	100 (9.29)	25 (7.62)	113 (51.3)
110-08-728	1/8 (3.20)	72 (1828.8)	210 (19.51)	35 (10.66)	238 (108.0)
110-12-368 ¹	3/16 (4.80)	36 (914.4)	150 (13.93)	50 (15.24)	254 (115.2)
110-12-488 ¹	3/16 (4.80)	48 (1219.2)	140 (13.00)	35 (10.66)	237 (107.5)
110-16-368	1/4 (6.35)	36 (914.4)	105 (9.75)	35 (10.66)	237 (107.5)
110-16-488	1/4 (6.35)	48 (1219.2)	100 (9.29)	25 (7.62)	226 (102.5)
110-16-728 ¹	1/4 (6.35)	72 (1828.8)	120 (11.15)	20 (6.09)	271 (122.9)

¹ Made to order.