



AB-619

| | |
|---------|---------------------|
| GRADE | Industrial |
| FINISH | Fabric (both sides) |
| POWDER | No |
| TRIMMED | No |
| COLOR | Red |

TECHNICAL SPECIFICATIONS

SPECIFICATION ASTM D2000: 1AA806Z1 | Z1= HARDNESS 75 +/- 5 SHORE A
POLYMER: STYRENE-BUTADIENE (SBR)

| ASTM | DESCRIPTION | VALUE |
|---------------------------------------|--------------------------|--|
| | SPECIFIC GRAVITY (gr/cc) | 1.8 |
| D2240 | HARDNESS (shore A) | 75 +/- 5 |
| D412 | TENSILE (psi) | 600 min. |
| | ULTIMATE ELONGATION (%) | 100 min. |
| D395B | COMPRESSION SET | 22 hrs @ 70°C (158°F) 50% max. |
| D573 | HEAT AGING | 70 hrs @ 70°C (158°F) Changed Hardness: +/-15 points max. Tensile: +/-30% max. Elongation: -50% max. |
| TEMPERATURE RANGE (general guideline) | | -20° to 180°F (-29° to 82°C) |

Maximum pieces per roll: 2 (100 pound rolls = 1 piece)

Minimum piece length: 5'

Width tolerance: -0.5 / +1"

Material is within commercial sheet rubber gauge tolerances.

Please ensure the product meets your application specification prior to order placement. Specifications are subject to change without notice. The website version prevails.

AB-619

| | GAUGE IN (MM) | WIDTH IN (MM) | SURFACE/ROLL SFT (M ²) | LENGTH/ROLL LFT (M) | WEIGHT/ROLL LBS (KG) |
|-------------------------|------------------|------------------|---------------------------------------|------------------------|-------------------------|
| 261-04-362 | 1/16 (1.60) | 36 (914.4) | 330 (30.66) | 110 (33.53) | 159 (72.1) |
| 261-04-366 | 1/16 (1.60) | 36 (914.4) | 200 (18.58) | 66.6 (20.29) | 96 (43.5) |
| 261-04-482 | 1/16 (1.60) | 48 (1219.2) | 320 (29.73) | 80 (24.38) | 153 (69.4) |
| 261-06-362 | 3/32 (2.38) | 36 (914.4) | 225 (20.90) | 75 (22.85) | 176 (79.8) |
| 261-06-366 ¹ | 3/32 (2.38) | 36 (914.4) | 126 (11.71) | 42 (12.8) | 99 (44.9) |
| 261-06-482 ¹ | 3/32 (2.38) | 48 (1219.2) | 220 (20.43) | 55 (16.76) | 172 (78.0) |
| 261-08-362 | 1/8 (3.20) | 36 (914.4) | 165 (15.33) | 55 (16.76) | 173 (78.5) |
| 261-08-366 | 1/8 (3.20) | 36 (914.4) | 96 (8.91) | 32 (9.75) | 101 (45.8) |
| 261-08-482 | 1/8 (3.20) | 48 (1219.2) | 160 (14.86) | 40 (12.19) | 167 (75.7) |
| 261-08-486 | 1/8 (3.20) | 48 (1219.2) | 94 (8.73) | 23.5 (7.16) | 100 (45.4) |
| 261-12-362 ¹ | 3/16 (4.80) | 36 (914.4) | 120 (11.15) | 40 (12.19) | 185 (83.9) |
| 261-12-366 ¹ | 3/16 (4.80) | 36 (914.4) | 59 (5.48) | 19.6 (5.97) | 92 (41.7) |
| 261-12-482 | 3/16 (4.80) | 48 (1219.2) | 120 (11.15) | 30 (9.14) | 184 (83.5) |
| 261-16-362 | 1/4 (6.35) | 36 (914.4) | 90 (8.36) | 30 (9.14) | 191 (86.6) |
| 261-16-366 | 1/4 (6.35) | 36 (914.4) | 46 (4.27) | 15 (4.57) | 97 (44.0) |
| 261-16-482 | 1/4 (6.35) | 48 (1219.2) | 80 (7.43) | 20 (6.09) | 169 (76.7) |

¹ Made to order.