



# AB-2102 SBR CLOTH INSERTED PACKING

GRADE	Industrial
FINISH	Smooth
POWDER	Yes
TRIMMED	Yes
COLOR	Black
FABRIC	Polyester

## TECHNICAL SPECIFICATIONS

**SPECIFICATION ASTM D2000: 2AA607A13**  
**POLYMER: STYRENE-BUTADIENE (SBR)**

ASTM	DESCRIPTION	VALUE
	SPECIFIC GRAVITY (gr/cc)	1.33
D2240	HARDNESS (shore A)	60
D412	TENSILE (psi)	700 min.
	ULTIMATE ELONGATION (%)	250 min.
D395B	COMPRESSION SET	22 hrs @ 70°C (158°F) 50% max.
D573	HEAT AGING	70 hrs @ 70°C (158°F) Changed Hardness: +/-15 points max. Tensile: +/-30% max. Elongation: -50% max.
TEMPERATURE RANGE (general guideline)		-20° to 180°F (-29° to 82°C)

**Mullen Burst 1 Ply: 300 psi typical**  
**Maximum pieces per roll: 2 (Exception: 1/8 x 72 = 3 pieces)**  
**Minimum piece length: 10'**  
**Width tolerance: -0 / +1"**  
**Fabric 2 oz. polyester**  
**Material is within commercial sheet rubber gauge tolerances.**

Typical values do not constitute a specification.  
Please ensure the product meets your application specification prior to order placement.  
Specifications are subject to change without notice. The website version prevails.

# AB-2102

## SBR CLOTH INSERTED PACKING

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M <sup>2</sup> )	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
112-04-362	1/16 (1.60) 1 PLY	36 (914.4)	300 (27.87)	100 (30.48)	124 (56.2)
112-04-482	1/16 (1.60) 1 PLY	48 (1219.2)	400 (37.16)	100 (30.48)	166 (75.3)
112-08-362	1/8 (3.20) 1 PLY	36 (914.4)	150 (13.93)	50 (15.24)	129 (58.5)
112-08-482	1/8 (3.20) 1 PLY	48 (1219.2)	200 (18.58)	50 (15.24)	172 (78.0)
112-08-722	1/8 (3.20) 1 PLY	72 (1828.8)	300 (27.87)	50 (15.24)	257 (116.6)
112-12-362	3/16 (4.80) 2 PLY	36 (914.4)	120 (11.15)	40 (12.19)	149 (67.6)
112-12-482	3/16 (4.80) 2 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	198 (89.8)
112-16-362	1/4 (6.35) 3 PLY	36 (914.4)	120 (11.15)	40 (12.19)	199 (90.3)
112-16-482	1/4 (6.35) 3 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	266 (120.7)
112-16-722 <sup>1</sup>	1/4 (6.35) 3 PLY	72 (1828.8)	240 (22.29)	40 (12.19)	394 (178.7)
116-08-362	1/8 (3.20) 2 PLY	36 (914.4)	150 (13.93)	50 (15.24)	123 (55.8)
116-08-482	1/8 (3.20) 2 PLY	48 (1219.2)	200 (18.58)	50 (15.24)	163 (73.9)
116-12-362 <sup>1</sup>	3/16 (4.80) 3 PLY	36 (914.4)	120 (11.15)	40 (12.19)	148 (67.1)
116-12-482	3/16 (4.80) 3 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	197 (89.4)
116-16-362 <sup>1</sup>	1/4 (6.35) 4 PLY	36 (914.4)	120 (11.15)	40 (12.19)	197 (89.4)
116-16-482	1/4 (6.35) 4 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	263 (119.3)

<sup>1</sup> Made to order.