



IM-2100 SBR CLOTH INSERTED PACKING

GRADE	Commercial
FINISH	Smooth
POWDER	No
TRIMMED	Yes
COLOR	Black
FABRIC	Nylon

TECHNICAL SPECIFICATIONS

SPECIFICATION ASTM D2240 | Z1= HARDNESS 65 +/-7 SHORE A
POLYMER: STYRENE-BUTADIENE (SBR)

ASTM	DESCRIPTION	VALUE
D2240	HARDNESS (shore A)	65 +/- 7
D412	TENSILE (psi)	500 typical
	ULTIMATE ELONGATION (%)	250 min.
TEMPERATURE RANGE (general guideline)		-20° to 180°F (-29° to 82°C)

Mullen Burst 1 Ply: 300 psi typical

Maximum pieces per roll: 1

Width tolerance: +/-1"

Fabric: Nylon

Durometer tolerance +/-7

Material is within commercial sheet rubber gauge tolerances.

Typical values do not constitute a specification.

Please ensure the product meets your application specification prior to order placement.

Specifications are subject to change without notice. The website version prevails.

Physical properties based on rubber only.

IM-2100

SBR CLOTH INSERTED PACKING

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M ²)	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
101-04-362	1/16 (1.60) 1 PLY	36 (914.4)	300 (27.87)	100 (30.48)	148 (67.1)
101-04-482	1/16 (1.60) 1 PLY	48 (1219.2)	400 (37.16)	100 (30.48)	197 (89.3)
101-08-362	1/8 (3.20) 2 PLY	36 (914.4)	150 (13.93)	50 (15.24)	147 (66.9)
101-08-482	1/8 (3.20) 2 PLY	48 (1219.2)	200 (18.58)	50 (15.24)	197 (89.3)
101-12-362	3/16 (4.80) 3 PLY	36 (914.4)	120 (11.15)	40 (12.19)	177 (80.2)
101-12-482	3/16 (4.80) 3 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	236 (107.0)
101-16-362	1/4 (6.35) 4 PLY	36 (914.4)	120 (11.15)	40 (12.19)	236 (107.0)
101-16-482	1/4 (6.35) 4 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	315 (142.7)
102-08-362	1/8 (3.20) 1 PLY	36 (914.4)	150 (13.93)	50 (15.24)	148 (66.9)
102-08-482	1/8 (3.20) 1 PLY	48 (1219.2)	200 (18.58)	50 (15.24)	197 (89.2)
102-12-362	3/16 (4.80) 2 PLY	36 (914.4)	120 (11.15)	40 (12.19)	177 (80.3)
102-12-482	3/16 (4.80) 2 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	236 (107.0)
102-16-362	1/4 (6.35) 3 PLY	36 (914.4)	120 (11.15)	40 (12.19)	236 (107.0)
102-16-482	1/4 (6.35) 3 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	315 (412.8)