



AB-135

GRADE	Premium
FINISH	Smooth
POWDER	Yes
TRIMMED	Yes
COLOR	Tan

TECHNICAL SPECIFICATIONS

SPECIFICATION ASTM D2000: 2AA425A13F17
 POLYMER: NATURAL RUBBER (NR)

ASTM	DESCRIPTION	VALUE
	SPECIFIC GRAVITY (gr/cc)	1.06
D2240	HARDNESS (shore A)	40
D412	TENSILE (psi)	2500 min.
	ULTIMATE ELONGATION (%)	400 min.
	DIN ABRASION METHOD 53516	Wet: 39 mm ³ Dry: 176 mm ³
D2137	COLD TEMPERATURE	-40°C/°F min.
D395B	COMPRESSION SET	22 hrs @ 70°C (158°F) 50% max.
D573	HEAT AGING	70 hrs @ 70°C (158°F) Changed Hardness: 15 points max. Tensile: +/-30% max. Elongation: -50% max.
TEMPERATURE RANGE (general guideline)		-20° to 180°F (-29° to 82°C)

Maximum pieces per roll: 2

Minimum piece length: 10'

Width tolerance: -0 / +1"

Material is within commercial sheet rubber gauge tolerances.

Please ensure the product meets your application specification prior to order placement.
 Specifications are subject to change without notice. The website version prevails.

AB-135

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M ²)	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
127-04-362 ¹	1/16 (1.60)	36 (914.4)	300 (27.87)	100 (30.48)	97 (44.0)
127-04-482 ¹	1/16 (1.60)	48 (1219.2)	400 (37.16)	100 (30.48)	130 (58.9)
127-06-362 ¹	3/32 (2.38)	36 (914.4)	225 (20.90)	75 (22.85)	113 (51.3)
127-06-482 ¹	3/32 (2.38)	48 (1219.2)	300 (27.87)	75 (22.85)	152 (68.9)
127-08-362	1/8 (3.20)	36 (914.4)	150 (13.93)	50 (15.24)	108 (49.0)
127-08-482	1/8 (3.20)	48 (1219.2)	200 (18.58)	50 (15.24)	144 (65.3)
127-12-362 ¹	3/16 (4.80)	36 (914.4)	120 (11.15)	40 (12.19)	123 (55.8)
127-12-482	3/16 (4.80)	48 (1219.2)	160 (14.86)	40 (12.19)	164 (74.4)
127-16-362	1/4 (6.35)	36 (914.4)	120 (11.15)	40 (12.19)	164 (74.4)
127-16-482	1/4 (6.35)	48 (1219.2)	160 (14.86)	40 (12.19)	219 (99.3)
127-24-362 ¹	3/8 (9.50)	36 (914.4)	90 (8.36)	30 (9.14)	183 (83.0)
127-24-482	3/8 (9.50)	48 (1219.2)	120 (11.15)	30 (9.14)	243 (110.2)
127-32-362	1/2 (12.70)	36 (914.4)	150 (13.93)	50 (15.24)	407 (184.6)
127-32-482	1/2 (12.70)	48 (1219.2)	200 (18.58)	50 (15.24)	542 (245.8)
127-48-362 ¹	3/4 (19.00)	36 (914.4)	90 (8.36)	30 (9.14)	361 (163.7)
127-48-488 ¹	3/4 (19.00)	48 (1219.2)	120 (11.15)	30 (9.14)	481 (218.2)
127-64-368	1 (25.40)	36 (914.4)	90 (8.36)	30 (9.14)	486 (220.4)

¹ Made to order.