



**IM-S60**

GRADE	Industrial
FINISH	Smooth
POWDER	No
TRIMMED	Yes
COLOR	Terracotta red

**TECHNICAL SPECIFICATIONS**

SPECIFICATION ASTM D2240 | Z1= HARDNESS 60 +/-5 SHORE A  
POLYMER: SILICONE RUBBER

ASTM	DESCRIPTION	VALUE
D2240	HARDNESS (shore A)	60 +/- 5
D412	TENSILE (psi)	800 typical
	ULTIMATE ELONGATION (%)	400 typical
TEMPERATURE RANGE (general guideline)		-80° to 450°F (-62° to 232°C)

**The maximum temperature is for instantaneous and not continuous applications.  
Material is within commercial sheet rubber gauge tolerances.**

Typical values do not constitute a specification.  
Please ensure the product meets your application specification prior to order placement.  
Specifications are subject to change without notice. The website version prevails.

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M <sup>2</sup> )	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
861-04-362	1/16 (1.60)	36 (914.4)	150 (13.93)	50 (15.24)	61 (27.9)
861-04-368	1/16 (1.60)	36 (914.4)	30 (9.14)	10 (3.05)	12 (5.4)
861-08-362	1/8 (3.20)	36 (914.4)	150 (13.93)	50 (15.24)	123 (55.8)
861-08-368	1/8 (3.20)	36 (914.4)	30 (9.14)	10 (3.05)	25 (11.3)
861-08-482	1/8 (3.20)	48 (1219.2)	200 (18.58)	50 (15.24)	164 (74.4)
861-08-488	1/8 (3.20)	48 (1219.2)	40 (12.20)	10 (3.05)	33 (14.9)
861-16-362	1/4 (6.35)	36 (914.4)	150 (13.93)	50 (15.24)	246 (111.6)
861-16-368	1/4 (6.35)	36 (914.4)	30 (9.14)	10 (3.05)	49 (22.2)