



IM-S60

GRADE	Industrial
FINISH	Smooth
POWDER	No
TRIMMED	Yes
COLOR	Terracotta red

TECHNICAL SPECIFICATIONS

SPECIFICATION ASTM D2240 | Z1= HARDNESS 60 +/-5 SHORE A
POLYMER: SILICONE RUBBER

ASTM	DESCRIPTION	VALUE
D2240	HARDNESS (shore A)	60 +/- 5
D412	TENSILE (psi)	800 typical
	ULTIMATE ELONGATION (%)	400 typical
TEMPERATURE RANGE (general guideline)		-80° to 450°F (-62° to 232°C)

The maximum temperature is for instantaneous and not continuous applications.

Material is within commercial sheet rubber gauge tolerances.

The documentation for sheet rubber gauge tolerances is published on our website. Typical values do not constitute a specification.

Please ensure the product meets your application specification prior to order placement. Specifications are subject to change without notice. The website version prevails.

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M ²)	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
861-04-362	1/16 (1.60)	36 (914.4)	150 (13.93)	50 (15.24)	61 (27.9)
861-04-368 ¹	1/16 (1.60)	36 (914.4)	30 (9.14)	10 (3.05)	12 (5.4)
861-08-362	1/8 (3.20)	36 (914.4)	150 (13.93)	50 (15.24)	123 (55.8)
861-08-368 ¹	1/8 (3.20)	36 (914.4)	30 (9.14)	10 (3.05)	25 (11.3)
861-08-482	1/8 (3.20)	48 (1219.2)	200 (18.58)	50 (15.24)	164 (74.4)
861-08-488 ¹	1/8 (3.20)	48 (1219.2)	40 (12.20)	10 (3.05)	33 (14.9)
861-16-362	1/4 (6.35)	36 (914.4)	150 (13.93)	50 (15.24)	246 (111.6)
861-16-368	1/4 (6.35)	36 (914.4)	30 (9.14)	10 (3.05)	49 (22.2)

¹ Made to order.