



IM-165 SKIRTBOARD

GRADE	Industrial
FINISH	Smooth
POWDER	No
TRIMMED	Yes
COLOR	Black

TECHNICAL SPECIFICATIONS

SPECIFICATION ASTM D2240 | Z= HARDNESS 60 +/-7 SHORE A
POLYMER: STYRENE-BUTADIENE (SBR)

ASTM	DESCRIPTION	VALUE
D2240	HARDNESS (shore A)	60 +/- 7
D412	TENSILE (psi)	1000 typical
	ULTIMATE ELONGATION (%)	300 typical
TEMPERATURE RANGE (general guideline)		-20° to 180°F (-29° to 82°C)

Maximum pieces per roll: 1

Width tolerance: +/-0.177"

Durometer tolerance: +/-7 points

Material is within commercial sheet rubber gauge tolerances.

Typical values do not constitute a specification.

Please ensure the product meets your application specification prior to order placement.

Specifications are subject to change without notice. The website version prevails.

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M ²)	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
163-66-084	1 1/2 (38.10)	8 (203.2)	50 (4.65)	50 (15.24)	327 (148.3)
163-66-104	1 1/2 (38.10)	10 (254.0)	50 (4.65)	50 (15.24)	410 (186.0)
163-66-124	1 1/2 (38.10)	12 (304.8)	50 (4.65)	50 (15.24)	492 (223.2)