



AmericanBiltrite
Flooring

**MARATHON® ROUND™, NATURAL SLATE™, DESERT STONE®, LAKELAND SLATE®
RUBBER TILE FLOOR**

TECHNICAL SPECIFICATIONS

	Metric	Imperial
Gauge	3 mm	0.118"
Sizes	906 mm x 906 mm 452 mm x 452 mm Micro Ground™	35.687" x 35.687" 17.798" x 17.798" Micro Ground™
Product Classification: ASTM F1344 - Rubber Tile Floor	Type I, A or B (Homogeneous)	
ASTM D2047 – Static Coefficient of Friction (leather/Neolite)	≥ 0.5	
ASTM D3389 – Abrasion Resistance (H-18 500 g @ 1,000 cycles)	Pass	
ASTM E648 – Critical Radiant Flux CRF (W/cm ²)	≥ 0.45	
ASTM E662 – Smoke Density	≤ 450	
ASTM F925 – Chemical Resistance	Meets requirements (details upon request)	
ASTM F970 – Static Load	≤ 0.005"	
ASTM F1514 – Heat Stability	ΔE ≤ 8.0	
ASTM G21 – Antimicrobial Resistance Test	Pass (28 days)	
Indoor Air Quality (IAQ): Volatile Organic Compounds (VOC's)	FloorScore Certified by SCS Certification Registration Number SCS-FS-01492	
New York City Fire Prevention Code	Accepted under section 27-348	
New York State Fire Prevention Code	Filed in compliance with Article 15, Part 1120	
Adhesives: AD-777 AD-590	Regular traffic Heavy rolling loads	
Limited Wear Warranty	10 years	
Resistance to oils and greases		
Marathon is not recommended for environments where it could be exposed to oils and greases, whether mineral, animal or vegetable.		
Antimicrobial		
IMPORTANT: All Marathon Rubber Flooring, through its composition and without the use of antimicrobial chemicals, does not promote microbial growth.		

Please note that technical web site documents prevail.

