



# AB-984 SBR CLOTH INSERTED PACKING

GRADE	Industrial
FINISH	Smooth
POWDER	Yes
TRIMMED	Yes
COLOR	Black
FABRIC	Polyester

## TECHNICAL SPECIFICATIONS

**SPECIFICATION ASTM D2000: 1AA805**  
**POLYMER: STYRENE-BUTADIENE (SBR)**

ASTM	DESCRIPTION	VALUE
	SPECIFIC GRAVITY (gr/cc)	1.51
D2240	HARDNESS (shore A)	80
D412	TENSILE (psi)	500 min.
	ULTIMATE ELONGATION (%)	100 min.
D395 (Method B)	COMPRESSION SET 22 hrs @ 70°C (158°F)	50% max.
D573	HEAT AGING 70 hrs @ 70°C (158°F)	Hardness: +/-15 Tensile (%): +/-30 max. Elongation (%): -50 max.
TEMPERATURE RANGE (general guideline)		-20° to 180°F (-29° to 82°C)

**Mullen Burst 1 Ply: 300 psi typical**

**Maximum pieces per roll: 2**

**Minimum piece length: 10'**

**Width tolerance: -0 / +1"**

**Fabric width tolerance: +/- 1"**

**Fabric 2 oz. polyester**

**Material is within commercial sheet rubber gauge tolerances.**

The documentation for sheet rubber gauge tolerances is published on our website.

Typical values do not constitute a specification.

Please ensure the product meets your application specification prior to order placement.

Specifications are subject to change without notice. The website version prevails.



# AB-984 SBR CLOTH INSERTED PACKING

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M <sup>2</sup> )	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
117-04-362	1/16 (1.60) 1 PLY	36 (914.4)	300 (27.87)	100 (30.48)	142 (64.4)
117-04-482	1/16 (1.60) 1 PLY	48 (1219.2)	400 (37.16)	100 (30.48)	189 (85.7)
117-06-362	3/32 (2.38) 1 PLY	36 (914.4)	225 (20.90)	75 (22.85)	159 (72.1)
117-06-482 <sup>1</sup>	3/32 (2.38) 1 PLY	48 (1219.2)	300 (27.87)	75 (22.85)	211 (95.7)
117-08-362	1/8 (3.20) 1 PLY	36 (914.4)	150 (13.93)	50 (15.24)	143 (64.9)
117-08-482	1/8 (3.20) 1 PLY	48 (1219.2)	200 (18.58)	50 (15.24)	190 (86.2)
117-12-362	3/16 (4.80) 2 PLY	36 (914.4)	120 (11.15)	40 (12.19)	170 (77.1)
117-12-482	3/16 (4.80) 2 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	227 (102.9)
117-16-362	1/4 (6.35) 2 PLY	36 (914.4)	120 (11.15)	40 (12.19)	229 (103.9)
117-16-482	1/4 (6.35) 2 PLY	48 (1219.2)	160 (14.86)	40 (12.19)	305 (138.3)
118-08-362	1/8 (3.20) 2 PLY	36 (914.4)	150 (13.93)	50 (15.24)	143 (64.9)
118-08-482	1/8 (3.20) 2 PLY	48 (1219.2)	200 (18.58)	50 (15.24)	191 (86.6)
118-08-722 <sup>1</sup>	1/8 (3.20) 2 PLY	72 (1828.8)	300 (27.87)	50 (15.24)	286 (129.7)

<sup>1</sup> Made to order.