



IM-272

GRADE	Commercial
FINISH	Smooth
POWDER	No
TRIMMED	Yes
COLOR	Black

TECHNICAL SPECIFICATIONS

SPECIFICATION ASTM D2240 | Z1= HARDNESS 70 +/-7 SHORE A
POLYMER: NEOPRENE (CR) BLEND

ASTM	DESCRIPTION	VALUE
D2240	HARDNESS (shore A)	70 +/-7
D412	TENSILE (psi)	500 typical
	ULTIMATE ELONGATION (%)	200 typical
TEMPERATURE RANGE (general guideline)		-20° to 190°F (-29° to 88°C)

Width tolerance: +/-0.5 "

Durometer tolerance: +/-7 points

Material is within commercial sheet rubber gauge tolerances.

Typical values do not constitute a specification.

Please ensure the product meets your application specification prior to order placement.

Specifications are subject to change without notice. The website version prevails.

IM-272

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M ²)	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
203-04-362	1/16 (1.60)	36 (914.4)	300 (27.87)	100 (30.48)	150 (68.0)
203-04-482	1/16 (1.60)	48 (1219.2)	400 (37.16)	100 (30.48)	200 (90.7)
203-06-362 ¹	3/32 (2.38)	36 (914.4)	225 (20.90)	75 (22.85)	225 (102.1)
203-06-482	3/32 (2.38)	48 (1219.2)	300 (27.87)	75 (22.85)	225 (102.1)
203-08-362	1/8 (3.20)	36 (914.4)	150 (13.93)	50 (15.24)	150 (68.0)
203-08-482	1/8 (3.20)	48 (1219.2)	200 (18.58)	50 (15.24)	200 (90.7)
203-12-362	3/16 (4.80)	36 (914.4)	120 (11.15)	40 (12.19)	180 (81.6)
203-12-482	3/16 (4.80)	48 (1219.2)	160 (14.86)	40 (12.19)	240 (108.8)
203-16-362	1/4 (6.35)	36 (914.4)	120 (11.15)	40 (12.19)	240 (108.8)
203-16-482	1/4 (6.35)	48 (1219.2)	160 (14.86)	40 (12.19)	320 (145.1)
203-24-362	3/8 (9.50)	36 (914.4)	90 (8.36)	30 (9.14)	270 (122.5)
203-24-482	3/8 (9.50)	48 (1219.2)	120 (11.15)	30 (9.14)	360 (163.3)
203-32-362	1/2 (12.70)	36 (914.4)	90 (8.36)	30 (9.14)	360 (163.3)
203-32-482	1/2 (12.70)	48 (1219.2)	120 (11.15)	30 (9.14)	480 (217.7)
203-40-362	5/8 (15.90)	36 (914.4)	90 (8.36)	30 (9.14)	450 (204.1)
203-40-482	5/8 (15.90)	48 (1219.2)	120 (11.15)	30 (9.14)	600 (272.2)
203-48-362	3/4 (19.00)	36 (914.4)	90 (8.36)	30 (9.14)	540 (244.9)
203-48-482	3/4 (19.00)	48 (1219.2)	120 (11.15)	30 (9.14)	720 (326.6)
203-64-362	1 (25.40)	36 (914.4)	90 (8.36)	30 (9.14)	720 (326.6)
203-64-482	1 (25.40)	48 (1219.2)	100 (9.29)	25 (7.62)	800 (362.9)

¹ Made to order.