



FLAME-GUARD



| | |
|---------|---------|
| GRADE | Premium |
| FINISH | Smooth |
| POWDER | No |
| TRIMMED | Yes |
| COLOR | Black |

TECHNICAL SPECIFICATIONS

SPECIFICATION ASTM D2000: 2BC625B14C12F17
 POLYMER: POLYCHLOROPRENE, NEOPRENE TEXTURED BONDING LAYER (CR)

| ASTM | DESCRIPTION | VALUE |
|---------------------------------------|--------------------------|---|
| | SPECIFIC GRAVITY (gr/cc) | 1.25 |
| D2240 | HARDNESS (shore A) | 60 |
| D412 | TENSILE (psi) | 2500 min. |
| | ULTIMATE ELONGATION (%) | 400 min. |
| D2137 | COLD TEMPERATURE | -40°C/°F min. |
| D395B | COMPRESSION SET | 22 hrs @ 100°C (212°F) 35% max. |
| D573 | HEAT AGING | 70 hrs @ 100°C (212°F) Changed Hardness: +/-15 points max. Tensile: +/-30% max. Elongation: -50% max. |
| D1149 | OZONE RESISTANCE | 100 hrs @ 37.7°C (99.86°F) @ 100 ppm No cracks |
| D471 | OIL AGING #3 | 70 hrs @ 100°C (212°F) Volume changed: 120% max. |
| CMVSS 302 FMVSS 302 | FLAMMABILITY | Does not ignite or is self-extinguishing |
| C1166 | FLAME PROPAGATION | Pass |
| TEMPERATURE RANGE (general guideline) | | -40° to 250°F (-40° to 121°C) |

Maximum pieces per roll: 2
Minimum piece length: 10'
Width tolerance: -0 / +1"
Technical specifications are for the product without the bonding layer.
Material is within commercial sheet rubber gauge tolerances.

Please ensure the product meets your application specification prior to order placement.
 Specifications are subject to change without notice. The website version prevails.

FLAME-GUARD



| | GAUGE IN (MM) | WIDTH IN (MM) | SURFACE/ROLL SFT (M ²) | LENGTH/ROLL LFT (M) | WEIGHT/ROLL LBS (KG) |
|-------------------------|------------------|------------------|---------------------------------------|------------------------|-------------------------|
| 320-16-482 ¹ | 1/4 (6.35) | 48 (1219.2) | 140 (13.00) | 35 (10.67) | 229 (103.9) |
| 320-24-482 ¹ | 3/8 (9.50) | 48 (1219.2) | 140 (13.00) | 35 (10.67) | 343 (155.6) |
| 320-32-482 ¹ | 1/2 (12.70) | 48 (1219.2) | 140 (13.00) | 35 (10.67) | 458 (207.7) |

¹ Made to order.