



AB-138



GRADE	Industrial
FINISH	Smooth
POWDER	Yes
TRIMMED	Yes
COLOR	Beige

TECHNICAL SPECIFICATIONS

SPECIFICATION ASTM D2000: 2AA420A13F17 | FDA COMPLIANT
POLYMER: NATURAL RUBBER (NR)

ASTM	DESCRIPTION	VALUE	
	SPECIFIC GRAVITY (gr/cc)	1.14	
D2240	HARDNESS (shore A)	40	
D412	TENSILE (psi)	2000 min.	2500 typical
	ULTIMATE ELONGATION (%)	400 min.	700 typical
D2137	COLD TEMPERATURE	-40°C/°F min.	
D395B	COMPRESSION SET	22 hrs @ 70°C (158°F) 50% max.	
D573	HEAT AGING	70 hrs @ 70°C (158°F) Changed Hardness: 15 points max. Tensile: +/-30% max. Elongation: -50% max.	
TEMPERATURE RANGE (general guideline)		-20° to 180°F (-29° to 82°C)	

Maximum pieces per roll: 2

Minimum piece length: 10'

Width tolerance: -0 / +1"

Material is within commercial sheet rubber gauge tolerances.

Meets the requirements for FDA 21 CFR 177.2600: "Rubber articles intended for repeated use may be safely used in producing, manufacturing, packing, processing, preparing, treating, packaging, transporting, or holding food, subject to the provisions of this section."

Typical values do not constitute a specification.

Please ensure the product meets your application specification prior to order placement.

Specifications are subject to change without notice. The website version prevails.

AB-138



	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M ²)	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
128-04-362	1/16 (1.60)	36 (914.4)	300 (27.87)	100 (30.48)	106 (48.1)
128-04-482	1/16 (1.60)	48 (1219.2)	400 (37.16)	100 (30.48)	141 (63.9)
128-06-362 ¹	3/32 (2.38)	36 (914.4)	225 (20.90)	75 (22.85)	121 (54.9)
128-06-482 ¹	3/32 (2.38)	48 (1219.2)	300 (27.87)	75 (22.85)	161 (73.0)
128-08-362	1/8 (3.20)	36 (914.4)	150 (13.93)	50 (15.24)	117 (53.1)
128-08-482	1/8 (3.20)	48 (1219.2)	200 (18.58)	50 (15.24)	156 (70.8)
128-12-362	3/16 (4.80)	36 (914.4)	120 (11.15)	40 (12.19)	134 (60.8)
128-12-482	3/16 (4.80)	48 (1219.2)	160 (14.86)	40 (12.19)	178 (80.7)
128-16-362	1/4 (6.35)	36 (914.4)	120 (11.15)	40 (12.19)	178 (80.7)
128-16-482	1/4 (6.35)	48 (1219.2)	160 (14.86)	40 (12.19)	237 (107.5)
128-24-362 ¹	3/8 (9.50)	36 (914.4)	90 (8.36)	30 (9.14)	198 (89.8)
128-24-482	3/8 (9.50)	48 (1219.2)	120 (11.15)	30 (9.14)	264 (119.7)
128-32-362	1/2 (12.70)	36 (914.4)	150 (13.93)	50 (15.24)	441 (200.0)
128-32-482	1/2 (12.70)	48 (1219.2)	200 (18.58)	50 (15.24)	588 (266.7)
128-40-362 ¹	5/8 (15.90)	36 (914.4)	90 (8.36)	30 (9.14)	331 (150.1)
128-40-482	5/8 (15.90)	48 (1219.2)	120 (11.15)	30 (9.14)	441 (200.0)
128-48-362	3/4 (19.00)	36 (914.4)	90 (8.36)	30 (9.14)	392 (177.8)
128-48-482	3/4 (19.00)	48 (1219.2)	120 (11.15)	30 (9.14)	522 (236.8)
128-64-362	1 (25.40)	36 (914.4)	90 (8.36)	30 (9.14)	528 (239.5)
128-64-482	1 (25.40)	48 (1219.2)	100 (9.29)	25 (7.62)	588 (266.7)

¹ Made to order.